


| | | | | |
|-----------------|-----------------|--|--|---------------------|
| TANK OPENING: | 2.56" | 1. CORRECT CURRENT AND BIL RATING (MAY 1/02) |  CROSSLINK TECHNOLOGY INC. | |
| CONDUCTOR: | MACHINED COPPER | | | |
| PLATING: | TIN | | | |
| MATERIAL: | OUTDOOR EPOXY | | | |
| STD. COLOUR: | GREY | | | |
| CURRENT RATING: | 1600 AMPS | IMPORTANT All information supplied by Crosslink Technology Inc. is furnished upon the express condition that the person receiving the product shall make his own assessments to determine its suitability for his particular purpose. No warranty is expressed or implied regarding such information or product; the results to be obtained from the use thereof, any product, as to its being merchantable or fit for any particular purpose, the use of such information or product not infringing any patent. | TITLE: 90-209 | REVISION: 1 |
| B.I.L. | 30 k.V. | | DESCRIPTION: L.V. BUSHING | |
| VOLTAGE CLASS: | 1.2 k.V. | | DIMMENSIONS: INCHES | SCALE: NOT TO SCALE |
| OTHER: | | | DATE: OCT.13/93 | SIGNED: |
| | | | TOLERANCE: 0.000 = +/- 0.005 ; 0.00 = +/- 0.05 UNLESS OTHERWISE SPECIFIED | |